








Cargo Slider Attachment Bracket Installation and Service Parts

Jeep Wrangler (JL) – 4 Door, 2018 and up

Kit Contents:

Part Number	Description	Quantity	Image
5012122A	Hardware	1	
			
5012989A	Bracket – Slider Mount Front JL	1	
5012990A	Bracket – Slider Mount Rear JL	1	

Required Tools:

Description	Image
Socket Wrench	
10 mm Socket (if installing slider)	
T-40 Driver Handle or Socket	

INSTALLATION

NOTE: Before proceeding, make sure to remove and relocate the Factory Jack Assembly located in the Rear Storage Compartment to ensure ease of access during an emergency situation.

Step 1 Remove Existing Hardware: Use a T40 Torx to remove the two front and two rear Luggage Retainers from the both Bin Trim Systems (Figure 1). In case of Trail Rail (not shown) remove the front and rear Attachment Bolts from both Rails, depending on the number and position of Slide Systems to be installed you may also need to reposition and/or remove the Trail Rail Trolleys

Step 2 Install Brackets: Position the Front and Rear Slider Brackets as shown (Figure 2), Be sure the larger Bracket is in the forward vehicle position and the arrows on both Brackets are pointing forward to the front of the vehicle. Use the M8 Hex Bolts to secure the Brackets to the vehicle.

Step 3 Install Slider (Sold Separately): Align the Slider in the desired position over the attachment points on the Slider Brackets (Figure 2), make sure the Slider is positioned so it will extend rearward in the vehicle. Use the M6 Hex Bolts to secure the Slider to the Brackets.

