

Category: Heater

Document Number: PI148TP

Date: 3/20/2019

Description: **Light- Medium-Duty fuel operated heater connection options**

Overview:

This bulletin has been released to assist installers in fuel making connections utilizing factory up-fitter ports.

Details:

When installing a Webasto fuel-fired heater in a light- or medium-duty vehicle you may be able to utilize the factory up-fitter port installed on or near the fuel tank. The table below will assist the installer in making that connection.

Vehicle	Aux Port Location	Parts Required	Notes
Ram ProMaster	On the sending unit	5012589A - Adapter 1319718A – Hose 1310763A – Clamp	There is an access cover between the seats to allow access to the sending unit
Ford Transit	On the sending unit	1319718A – Hose 1310763A – Clamp Adapter kit available through Ford dealer	Adapter kit adapts to mounting boss on sending unit. The fuel tank does not have to be removed, only lowered.
Mercedes Sprinter	Near fuel fill pipe	5012589A - Adapter 1319718A – Hose 1310763A – Clamp	The aux fuel port is part of the KL-1 group. In some years this was optional from the factory. The fuel tank does not need to be removed.

In some cases, the 5012589A adapter is not the most desirable option. Dorman Products (www.dormanproducts.com) has fuel adapters with other combinations of fittings and orientation. In all cases, be sure the fuel system is compliant with the requirements outlined in the installation manual.

If you have any questions, contact our technical support team at (800) 860-7866 or via email at: info-us@webasto.com.